

April 2007



**THE
Rental
STORE**

YANCEY

DOZERS

Model	Flywheel		Operating Wt.		Blade
	hp	kW	lbs.	kg	
D3 XL	70	52	16,125	7,314	VPAT Blade
D3 LGP	70	52	17,026	7,723	VPAT Blade
D4 XL	80	60	17,110	7,761	VPAT Blade
D4G	80	60	17,877	8,109	VPAT Blade
D5G XL	90	67	19,540	8,863	VPAT Blade
D5G LGP	90	67	20,298	9,207	VPAT Blade
D5N XL	110	82	25,800	8,800	VPAT Blade
D5N LGP	110	82	27,800	8,900	VPAT Blade
D6N XL	140	104	34,240	15,530	VPAT Blade
D6N LGP	140	104	37,320	16,930	VPAT Blade
D6R XL	175	130	42,300	19,200	SU, A Blade
D6R XL	175	130	48,550	22,072	PAT Blade
D6R LGP	185	138	45,600	20,700	S Blade
D7R	230	171	55,300	95,077	V,SU Blade
D8T	305	228	82,850	37,576	SU Blade
D9T	405	302	106,794	48,441	SU, U Blade
D10T	570	425	144,200	65,400	SU, U Blade

COMPACTORS

Model	Flywheel		Operating Wt.		Drum Width	
	hp	kW	lbs.	kg	in.	mm
CS-323C	80	60	9,985	4,540	50	1270
CP-323C	80	60	10,440	4,745	50	1270
CS-433C	105	78	14,675	6,670	66	1676
CP-433C	105	78	15,225	6,912	66	1676
CS-563D	145	107	24,700	11,215	84	2134
CP-563D	145	107	25,700	11,670	84	2134
CS-583C	145	107	33,500	15,230	84	2134
CB-214C	33	25	5,115	2,325	39.4	1000
CB-224C	33	25	5,335	2,425	47.2	1199
CB-634C	145	108	25,750	11,680	84	2130
815F	220	164	45,934	20,879	12'4"	3761
825G	315	235	69,828	31,740	15'2"	4614
826G	315	235	76,760	33,350	14'9"	4502

CS=Single Drum-Smooth CP=Single Drum-Padfoot CB=Double Drum-Smooth

TRACK LOADERS

Model	Flywheel		Operating Wt.		Bucket Range	
	hp	kW	lbs.	kg	cu. yds.	cu. m.
939C Hystat	90	67	21,500	9,750	1.50	1.20
953C	121	90	32,360	14,670	2.0-2.4	1.5-1.85
963C	160	119	41,940	19,020	2.5-3.2	1.9-2.45

BACKHOE LOADERS

Model	Flywheel		Operating Wt.		Dig Depth
	hp	kW	lbs.	kg	
416D-2WD*	75	58	12,257-21,605	6,900-9,800	14'5"/18'1"
416D-4WD	75	58	12,257-21,605	6,900-9,800	14'5"/18'1"
420D/IT	85	63	15,772-21,389	7,150-9,700	14'5"/18'1"

*these models also available for rent equipped with Hydraulic Hammers

EXCAVATORS

Model	Flywheel		Operating Wt.		Maximum	Reach/Depth
	hp	kW	lbs.	kg		
302.5	22.9	17.1	6,015	2,734	8'8" max.	2650 max.
303 CR	26	19.1	7,400	3,360	10'11" max.	3330 max.
303.5	25	19	7,810	3,550	10'10" max.	3690 max.
304C CR	25	19	10,582	4,800	10'5" max.	3160 max.
304.5	42	31	10,130	4,595	11'4" max.	3530 max.
305CR	42	31	11,000	4,990	12'11" max.	3930 max.
307C	55	41	15,895	7,210	22'1" / 15'3"	6731 / 4648
312CL*	90	67	29,150	14,100	28'4" / 19'10"	8636 / 6045
313B CR	89	66	29,155	13,225	28'1" / 19'6"	8550 / 5950
315CL*	99	74	37,000	16,700	30'0" / 21'6"	9144 / 6553
318CL*	119	89	40,540	18,390	30'4" / 20'0"	9240 / 6100
320CL*	138	103	46,300	21,000	35'1" / 25'1"	10.7 / 7.6
322CL	162	121	52,600	23,860	34'9" / 24'1"	10.6 / 7.3
325BL*	177	132	60,600	27,530	34'7" / 23'4"	10.5 / 7.1
330BL*	236	176	74,310	33,730	38'3" / 26'6"	11.7 / 8.1
345BLII	321	239	97,940	44,460	42'8" / 30'5"	13.0 / 9.3
365BL	385	287	149,000	67,630	46'1"	14.04

*these models also available for rent equipped with Hydraulic Hammers

SKID STEER LOADERS

Model	Flywheel		Operating Capacity	
	hp	kW	lbs.	kg
216B	49	36	1400	635
226B	57	42	1500	680
232B	49	36	1750	794
236B	70	51	1750	794
242B	57	42	2000	907
246B	78	57	2000	907
252B	70	51	2500	1134
262B	78	57	2700	1225

Work Tools Augers, Rock Hounds, Sweepers, Hammers and many more Skid Steer Loader tools.

*all models available with rubber tracks

WHEEL LOADERS

Model	Flywheel		Operating Wt.		Bucket Range	
	hp	kW	lbs.	kg	cu. yds.	cu. m.
906	68	51	10,912	4,960	1.0	.8
924G	105	78	20,081	9,100	1.8-2.25	1.4-1.7
928G	125	93	25,554	11,600	2.4-2.9	1.9-2.2
930G	149	112	28,725	13,029	2.6-6.5	2.1-5.0
938G	160	119	28,731	13,030	2.75-3.65	2.1-2.8
950G	180	134	39,200	17,782	3.25-4.5	2.5-3.5
962G	200	149	40,960	18,578	3.75-5.0	3.0-3.8
966G	235	175	50,410	22,865	4.25-5.25	3.3-4.0
972G	265	198	55,310	25,085	4.75-6.0	3.7-4.7
980G	300	224	65,078	29,519	5.0 - 7.5	3.8-5.7

Albany

1604 S. Slappey Blvd.
(229) 435-1300

Augusta

4165 Mike Padgett Hwy.
(706) 821-4280

Austell (Six Flags)

I-20 West & Six Flags Pkwy.
(770) 819-5208

Brunswick*

370 Perry Lane
(912) 265-5010

Calhoun

I-75 & Hwy. 41 (exit north)
(706) 879-2760

Columbus

I-185 & Smith Rd. (exit east)
(706) 649-0054

Cumming

1120 Pilgrim Road
(770) 205-1201

Dublin

Hwy. 257 & I-16 (exit south)
(478) 272-1661

Gwinnett (Dacula)

Hwy. 316 & Hurricane Trail
(678) 442-1982

SCRAPERS

Model	Flywheel		Operating Wt.		Bowl Capacities	
	hp	kW	lbs.	kg	cu.yd.	cu.m.
613C II	175	131	33,000	14,970	8.9/11	6.8/8.4
615C II	265	198	56,450	25,605	13/17	10/13
621G	330	246	71,090	32,250	14/20	10.7/15.3
623F	365	272	81,840	37,120	18/23	13.8/17.6
631F II	450-90	335-65	97,460	44,210	21/31	16.1/23.7

ARTICULATED TRUCKS

Model	Flywheel		Operating Wt.		Capacity	
	hp	kW	lbs.	kg	tons	m.t.
725	280	209	47,880	21,720	25	22.7
730	305	228	49,600	22,500	30	27.2
735	365	272	65,610	29,760	35	31.8
740	415	310	71,760	32,550	40	36.6

MOTORGRADERS

Model	Flywheel		Operating Wt.		Blade
	hp	kW	lbs.	kg	
135H	135	101	28,550	12,950	14'
12H	140	104	31,410	14,247	14'
140H	165	123	32,460	14,724	14'
LeeBoy 635	47	35	6,750	3,062	8'

TOOLCARRIERS

Model	Flywheel		Operating Wt.		Bucket Range	
	hp	kW	lbs.	kg	cu. yds.	cu. m.
IT24G	110	82	22,792	10,360	2.35	1.8
IT28G	125	93	26,526	12,030	2.0-4.5	1.5 - 3.5
IT38G	160	119	28,710	13,060	2.75-3.25	2.1-2.5
IT62G	200	149	40,380	18,314	4.0-4.25	3.1-3.3

TELEHANDLERS

Model	Flywheel		Operating Capacity	Lift Height
	hp	kW		
TH63	80	hp	6,000 lb.	41'
TH83	109	hp	8,000 lb.	41'
TH103	109	hp	10,000 lb.	44'
TH215	80	hp	5,500 lb.	18'
TH350	100	hp	6,600 lb.	36'
TH360	100	hp	7,000 lb.	44'
TH460	100	hp	8,800 lb.	44'
TH560	100	hp	11,000 lb.	44'

WELDERS

Towable	500 amp diesel
Portable	225 amp propane / gasoline

LIGHT PLANTS / ARROW BOARDS

Towable Lights	Four 1000 watt bulbs, 30' mast, 6kw generator, 30 hour run time
----------------	---

TAMPS & ROLLERS

Tamps	20" pad, 3375 ft./lbs., Vibratory Plate
Tamps	wide & narrow shoes up to 3025 ft./lbs.
Walk-Behind Compactors	22" & 32" wide drums, man. & remote control
Walk-Behind Roller	6" narrow trench roller
Ride-On Rollers (Vib.)	36" drum, water spray
Ride-On Trench Roller	33" drum, articulating

TRUCKS

Flatbed Trucks	16 ft., non-CDL
Dump Trucks	4/5 cubic yard, non-CDL
Water Trucks	2,000 gallon capacity

AERIAL LIFTS

20' Electric Scissor	33" width
25' Electric Scissor	46" width and 32" width
32' Electric Scissor	46" width
25' Push-around One-man Lift	
26' Rough Terrain Scissors	7'6" width dual fuel
40' & 45' Up/Over Electric	20' up/over clearance
40', 60' & 80' Boom Lifts	1000 lb. restricted platform capacity
Tow Behind Lifts	36" and 50' heights
45', 60' up & over Z-lift	rough terrain 4x4

WATER EQUIPMENT

Water Trucks	2,000 gallon capacity
Water Wagon	5,000 gallon capacity, 613 frame

SOIL STABILIZERS

Model	Flywheel	Operating Weight
SS-250B	335 h.p. 250kW	31,500 lbs. 14,288 kg

Kennesaw

2689 Barrett Lakes Blvd.
(678) 290-1248

Macon*

Pio Nono & Broadway
(478) 788-1773

McDonough

Hwy. 155 & Interstate South Dr.
(770) 819-5208

Savannah

1465 E. Highway 80
(912) 525-1206

Valdosta

2966 Hwy. 84, West
(229) 671-4720

*This location features only Caterpillar® equipment at this time.



Reach us from anywhere toll-free by calling
1-800-RENT-CAT

Look for us on the internet at
<http://www.YanceyRental.com>

PUMPS

2" Submersible	5,700 gph	55' total head
3" Centrifugal	25,000 gph	25' max. lift (90' max head)
3" Diaphragm	5,100 gph	25' max. lift
Sykes® GP100	600 gpm	4" suction/discharge
Sykes GP150	2,200 gpm	6" suction/discharge
Sykes GP200	3,200 gpm	8" suction/discharge
Sykes 300X	7,000 gpm	12" suction/discharge
Sykes UV0350	13,000 gpm	16" suction/discharge
Sykes UV0150	300 head feet	6" x 4" suction/discharge
Sykes UV0250	450 head feet	8" x 6" suction/discharge
Kanaflex® Suction Hose	4", 6", 8" & 12"	10 ft. & 20 ft. lengths
HD Layflat Discharge Hose	4", 6", 8" & 12"	50 ft. & 100 ft. lengths
Galvanized Pipe	4", 6", 8" & 12"	10 ft. & 20 ft. lengths
HDPE Fused Pipe	4" - 24"	all lengths
Hydrostatic Test Pump	2"	testing water & sewer lines
Test Plugs/Kits	8" - 60"	testing water & sewer lines
Sewer Plugs	8" - 60"	sewer bypass

TRENCHERS

Vermeer 1150 (walk behind)	24" boom w/trailer
Vermeer 3550 (ride-on)	40" boom, 6-way blade
Vermeer 5750 (ride-on)	48" boom, 6-way blade

HAMMERS & DRILLS

Hydraulic Hammers (backhoe/excavator mounted)	700#, 1000#, 2000#, #4000
Electric Breaker Hammers	60#
Electric Chipping Hammers	20#
Air Hammers	60#, 90#
Hand-Held Air Drills	

OTHER EQUIPMENT

Pressure Washers	2500 p.s.i. & 4000 p.s.i.
Kerosene & Propane Heaters	
Straw Blower - towable	
Ride-On Sweepers	8' boom, water spray
Towable Welders	500 amp diesel
Portable Welders	225 amp propane / gasoline

TRACTORS

Mini Backhoes
Bush Hogs
Tractors w/Box Blades

CONSUMABLES

Gloves	Coolers
Safety Supplies	Power Cords
Abrasive Blades	Fuel Cans
Diamond Blades	and MORE
Concrete Sprayers	

GENERATORS

6kW	Portable Generators
25kW	Towable Generators

The following Caterpillar generator units range in size from 30kW (XQ30) through 400 kW (XQ400). They are mounted on frames that can be towed behind trucks or other large vehicles.

XQ30	XQ45	XQ60	XQ75
XQ100	XQ125	XQ200	XQ230
XQ300	XQ350	XQ400	

The following Caterpillar generator units range in size from 500kW through 800 kw. These generators are built into self-enclosed containers that are transported by tractor-trailers.

XQ500	XQ600	XQ800
-------	-------	-------

These Caterpillar generators units range in size from 1000kW to 2000kW and are also built into self-enclosed containers that are transported by tractor-trailers. These Power Module units also contain automatic switch gear.

XQ1000	XQ1250	XQ1500
XQ1750	XQ2000	

FORKLIFTS

STRAIGHT-MAST "ROUGH TERRAIN" FORKLIFTS

Case 586 2-Wheel Drive	48" forks	side shift carriage	21.5' mast
Case 586 4-Wheel Drive	48" forks	side shift carriage	21.5' mast

WAREHOUSE FORKLIFTS

Caterpillar GP25	5,000 pound capacity
Caterpillar GP40	8,000 pound capacity

ALSO SEE TELESCOPIC HANDLERS ON OPPOSITE PAGE

AIR COMPRESSORS

Gasoline	8 c.f.m., portable
Diesel	185 c.f.m. - 375 c.f.m., towable

CONCRETE TOOLS

CONCRETE SAWS	12" & 14" Cutoff Saws
	14" & 16" Walk Behind Saws
VIBRATORS	1hp to 3 hp, 7/8" to 2-1/2" heads, 5' to 22' shafts
BLADES	Diamond & Abrasive Blades

